

Analog Hotplates, Stirrers & Hotplate Stirrers



Technical Data:

Hotplate (ES59301)

Temp. range:	80°C to 380°C
Platform:	7.1 x 7.1 in. (18 x 18 cm)
Control:	Quick adjustment knob
Dimensions (WxDxH):	8 x 10 x 4.5 in.
Electrical:	120V, 60Hz/230V, 50-60Hz

Magnetic Stirrer (ES59311)

Speed range:	60 to 1500 rpm
Platform:	7.1 x 7.1 in. (18 x 18 cm)
Control:	Quick adjustment knob
Dimensions (WxDxH):	8 x 10 x 4.5 in.
Electrical:	120V, 60Hz/230V, 50Hz

Hotplate Stirrer (ES59322)

Temp. range:	Amb. 80°C to 380°C
Speed Range:	60 to 1500 rpm
Platform:	7.1 x 7.1 in. (18 x 18 cm)
Control:	Quick adjustment knob
Dimensions (WxDxH):	8 x 10 x 4.5 in.
Electrical:	120V, 60Hz/230V, 50Hz

Features:

- Large, white ceramic top plate
- Compact, 8 x 10" footprint
- Three models; Hotplate, Stirrer and Hotplate Stirrer

Our hotplates, stirrers and hotplate-stirrers feature an exceptionally durable, chemical resistant white ceramic work surface. Their space-efficient design (8 x 9 in. footprint), makes them ideal for use on crowded benchtops and inside of bio-hoods.

Advanced microprocessor controls with convenient turn knobs allow quick, precise adjustment and maintenance of speed and temperature. Safety indicator LED's on the front panel indicate when the heating and/or stirring functions have been activated.

With a square 7.1 in work surface, all three models are compatible with a variety of popular sizes of borosilicate glass beakers, flasks, bottles and other vessels. The hotplate/magnetic stirrer model (ES59322) comes complete with a support rod for mounting thermometers and temperature probes.

Cat. No.	Description
ES59301	Hotplate, Analog w/ Ceramic Top
ES59311	Magnetic Stirrer, Analog w/ Ceramic Top
ES59322	Hotplate Magnetic Stirrer, Analog w/ Ceramic Top